

Type:
SCOpette P

Autoclavable Pipette

Single and multi-channel, fixed and variable volume



Features:

Single-channel pipette

- Fully autoclavable
- Lightweight, ergonomic, low force design
- Digital display clearly reads volume setting
- The pipettors cover the volume range from 0.1 ul to 5000ul
- Easy to calibrate and maintain with tool supplied
- Design helps avoid repetitive strain injuries
- Manufactured from modern innovative material

Multi-channel pipette

- 8- and 12-channel pipettes are available for standard 96-well plate
- Dispensing head rotates for optimum pipetting convenience
- Individual piston/tip cone assemblies allow easy repair and maintenance
- Compound material tip cone design allows visual seal verification
- Can be used with universal' style pipette tips.
- Calibrated in accordance with ISO/DIS 8655. Each pipette supplied with individual test certificate

Order
Informations:

Cat No.	Volume Range	Increment	Test Volume	Inaccuracy [±]	Imprecision [±]
Single-channel, Fixed Volume Pipette Type SCOpette P					
0.382.001	5µl		5µl	1.3%	1.2%
0.382.002	10µl		10µl	0.8%	0.8%
0.382.003	20µl		20µl	0.6%	0.5%
0.382.004	25µl		25µl	0.5%	0.3%
0.382.005	50µl		50µl	0.5%	0.3%
0.382.006	100µl		100µl	0.5%	0.3%
0.382.007	200µl		200µl	0.4%	0.2%
0.382.008	250µl		250µl	0.4%	0.2%
0.382.009	500µl		500µl	0.3%	0.2%
0.382.010	1000µl		1000µl	0.3%	0.2%
0.382.011	2000µl		2000µl	0.3%	0.15%
0.382.012	5000µl		5000µl	0.3%	0.15%
Single-channel, Variable Volume Pipette Type SCOpette P					
0.382.013	0.1-2.5 µl	0.05 µl	2.5 µl	2.50%	2.00%
			1.25 µl	3.00%	3.00%
			0.25 µl	12.00%	6.00%
0.382.014	0.5-10 µl	0.1 µl	10 µl	1.00%	0.80%
			5 µl	1.50%	1.50%
			1 µl	2.50%	1.50%
0.382.015	2-20 µl	0.5 µl	20 µl	0.90%	0.40%
			10 µl	1.20%	1.00%
			2 µl	3.00%	2.00%
0.382.016	5-50 µl	0.5 µl	50 µl	0.60%	0.30%
			25 µl	0.90%	0.60%
			5 µl	2.00%	2.00%
0.382.017	10-100 µl	1 µl	100 µl	0.80%	0.15%
			50 µl	1.00%	0.40%
			10 µl	3.00%	1.50%
0.382.018	20-200 µl	1 µl	200 µl	0.60%	0.15%
			100 µl	0.80%	0.30%
			20 µl	3.00%	1.00%
0.382.019	50-200 µl	1 µl	200 µl	0.60%	0.15%
			100 µl	0.80%	0.30%
			50 µl	1.00%	0.40%
0.382.020	100-1000 µl	5 µl	1000 µl	0.60%	0.20%
			500 µl	0.70%	0.25%
			100 µl	2.00%	0.70%
0.382.021	200-1000 µl	5 µl	1000 µl	0.60%	0.20%
			500 µl	0.70%	0.25%
			200 µl	0.90%	0.30%
0.382.022	1000-5000 µl	50 µl	5000 µl	0.50%	0.15%
			2500 µl	0.60%	0.30%
			1000 µl	0.70%	0.30%
8-channel, Variable Volume Pipette Type SCOpette P					
0.382.023	0.5-10 µl	0.1 µl	10 µl	1.50%	1.50%
			5 µl	2.50%	2.50%
			1 µl	4.00%	4.00%
0.382.024	5-50 µl	0.5 µl	50 µl	1.00%	0.50%
			25 µl	1.50%	1.00%
			5 µl	3.00%	2.00%
0.382.025	50-300 µl	5 µl	300 µl	0.70%	0.25%
			150 µl	1.00%	0.50%
			50 µl	1.50%	0.80%
12-channel, Variable Volume Pipette Type SCOpette P					
0.382.026	0.5-10 µl	0.1 µl	10 µl	1.50%	1.50%
			5 µl	2.50%	2.50%
			1 µl	4.00%	4.00%
0.382.027	5-50 µl	0.5 µl	50 µl	1.00%	0.50%
			25 µl	1.50%	1.00%
			5 µl	3.00%	2.00%
0.382.028	50-300 µl	5 µl	300 µl	0.70%	0.25%
			150 µl	1.00%	0.50%
			50 µl	1.50%	0.80%
Pipette Stand					
0.382.029	Linear Stand, holds up to 6 pipettors				
0.382.030	Round Stand, fits MicroPette Plus				



Address: S C O - T e c h Phon: + 49 (0) 36 075 / 43 439-0
 Auf der Heide 15 Fax: + 49 (0) 36 075 / 43 439-9
 D-37351 Dingelstädt E-mail: sco@sco-tech.com
 Federal Republic of Germany Internet: www.sco-tech.com

Contact